



## Bearing Rolamentos do Brasil Ltda.



7316BG Bearing 2D drawings and 3D CAD models

80,000 mm x 170,000 mm x 39,000 mm NATR  
35 PP Support Roller Bearing 35x72x28mm

Bearing No. 7316BG

Size	80x170x39 mm
Bore Diameter	80,000 mm
Outer Diameter	170,000 mm
Width	39,000 mm
d	80,000 mm
D	170,000 mm
B	39,000 mm
C	39,000 mm
a	72 mm
Contact angle	40 °
rs min	2.1 mm
r1s min	1.1 mm
Radial clearance class	CN
Mass	3.72 kg
Dynamic load, C	135 kN
Static load, C0	109 kN
Fatigue limit load, Cu	4.45 kN
Nlim (oil)	5,100 rpm
Nlim (grease)	3,800 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
da min	92 mm
db min	87 mm
Da max	158 mm



## Bearing Rolamentos do Brasil Ltda.

Db max	163 mm
r1a max	1 mm
ra max	2 mm
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	3.75
EAN	4547359452518
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	80MM Bore; 170MM Outside Diameter; 39MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1   ISO P0; No Filling Slot; No Snap Ring
Category	Angular Contact Ball Bearing
UNSPSC	31171531



## Bearing Rolamentos do Brasil Ltda.

Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	7316BG
Weight / LBS	8.265
Outside Diameter	6.693 Inch   170 Millimeter
Width	1.535 Inch   39 Millimeter
Bore	3.15 Inch   80 Millimeter
bore diameter:	80 mm
radial static load capacity:	109000 N
outside diameter:	170 mm
operating temperature range:	-40 to 120 ° C
overall width:	39 mm
cage material:	Steel
contact angle:	40 °
outer ring width:	39 mm
row type & fill slot:	Single-Row Non-Fill Slot
maximum rpm:	5100 rpm
internal clearance:	C0
finish/coating:	Uncoated
bore type:	Round
precision rating:	ISO Class 0
closure type:	Open
fillet radius:	2.1 mm
snap ring included:	Without Snap Ring
series:	73B
bearing material:	High Carbon Chrome Steel
weight:	3.740 kg
radial dynamic load capacity:	135000 N



## Bearing Rolamentos do Brasil Ltda.

manufacturer product page:

[Click here](#)